

SKYFIRE pro

TRUCK & BUS RADIAL TYRES



SK501AA



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	20	K	148/145	8.25	3150	2900	850	850	279	1056	17.50	320
12R22.5	22	K	152/149	9.00	4250	4000	900	900	300	1078	17.50	343
295/80R22.5	22	K	154/149	9.00	3750	3250	850	850	298	1049	17.50	335
315/70R22.5	20	K	158/150	9.00	4000	3350	900	900	314	1018	18.00	351
315/80R22.5	22	K	158/156	9.00	4250	4000	900	900	300	1078	17.50	351

SK512AA



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

Benefits




Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
295/80R22.5	22	L	154/149	9.00	3750	3250	850	850	298	1049	19.00	335
315/70R22.5	20	L	154/150	9.00	4000	3350	900	900	314	1018	20.00	351
315/80R22.5	22	L	158/156	9.00	4250	4000	900	900	300	1083	20.00	351

SK517AA



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance;
- Effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Off Road




Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	22	D	152/149	9.00	4250	4000	900	900	300	1087	22.00	343
315/80R22.5	22	D	158/156	9.00	4250	4000	900	900	300	1078	22.00	351

SK518AA



- Suitable for all wheel position of middle/long distance buses and steering wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	20	L	148/145	8.25	3150	2900	850	850	279	1054	16.50	320
12R22.5	22	L	152/149	9.00	4250	4000	900	900	300	1076	16.50	343
295/80R22.5	22	L	154/149	9.00	3750	3250	850	850	298	1044	16.50	335
315/70R22.5	20	L	154/150	9.00	4000	3350	900	900	314	1010	16.50	351
315/80R22.5	22	L	158/156	9.00	4250	4000	900	900	300	1076	16.50	351

SK537AA



- Suitable for drive positions.
- Mixed deep tread block, widened tread, increased grip performance.
- Design for on all road of non-paved roads.

Benefits



Regional



Off Road




Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
315/80R22.5	22	K	158/156	9.00	4250	4000	900	900	300	1081	19.00	351