


2025P1102



Long Haul/Regional/On & Off Road/Off Road/Coach & Urban

TRUCK&BUS TIRES

CATALOG 2025



JINYU TIRE GROUP
HQ Add:10th Floor,Block A,Platinum Plaza,No.5 Wenling Road,Laoshan District,Qingdao,China
Tel No.:0086-400-600-7809
E-mail:TBR2@jinyutires.com
Website:www.blacklontires.cn

Jinyu firmly adheres to the enterprise spirit, "Common benefit is above all" and the company's target of "Providing the customers with excellent quality products and a high level of service." We insist on focusing on our customer's demands, committing to our promises, operating ethically, and developing scientifically to maximize the common benefit of consumers, distributors, suppliers, employees, shareholders, communities, governments, enterprises and other related parties.

"Common benefit is above all"!

ENTERPRISE VISION

BLACKLION

TRUCK & BUS TIRE

Long Haul / Regional / On&Off Road / Off Road / Urban



To be the best tire supplier, trusted globally and able to provide the best value and experience to customers and end-users.

ENTERPRISE MISSION

Concentrate on rubber tire technology and service development and application; Commit ourselves to providing customers the best value and experience.



ENTERPRISE INTRODUCTION

Enterprise Profile

JINYU Tire Group Co., Ltd. was founded in 1995, which is a professional tire R & D and manufacturing enterprise. The company has total assets of 5.5billion Yuan and there are more than 6000 employees. By equipped with advanced tire production, research and development, testing equipment and professional technology, management team, the company has established a sound quality management system. There are two plants respectively located in China and Vietnam with total capacity of 8 million pcs/year. The company has set up sales centers in North America, Europe, Vietnam and other countries in local operation. The sales network covers more than 100 countries and regions in the Middle East, Asia, Europe, the United States, Africa and so on.

Jinyu Certificates

The company has obtained certificates like CCC, DOT, ECE, INMETRO, ISO/TS16949, GCC, SONCAP, TBS, SARS and so on. The company's laboratory has been certified by CNAS and ISO/IEC 17025 and obtained many national Patents.

Research and Development





The company believes proving excellent quality is a way of life and takes every opportunity to instill this value throughout the entire enterprise. As proof of this commitment, a considerable investment has been made in R&D over the last 20 years. The R&D center not only utilizes advanced equipment but also commits to having efficient operations and maintaining a strong teamwork culture. The team is hyper-focused on marketing, product planning, formula research and development, as well as, structure design and product testing.

CONTENTS

09 BF188	11 BT165	13 BT168	13 BF155	14 BD175
15 BD186	15 BD176	16 BD177	17 BD165	17 BD170
18 BD171	19 BD173	20 BT188	20 BT107	21 BT160
22 BT180	22 BT161	25 BD218	26 BD210	26 BD212
27 BD280	27 BD278	28 BD260	28 BD290	29 BLG19

30 BD215	30 BD216	33 BA202	33 BA208	34 BA267
35 BA111	35 BA115	36 BLR01	37 BA122	38 BA220
39 BA125	39 BA221	40 BA226	41 BA106	41 BA162
42 BA105	42 BA127	45 BD273	45 BD270	46 BD285
47 BD189	48 BD266	48 BD276	49 BLM16	50 BD263
50 BD265	53 BC121	53 BU123	54 BU551	54 BLC58
57 BW290	57 BW292	58 BW291		



Vehicle / Road	Long Haul	Regional	On & Off Road	Off Road	Coach & Urban
					
Steer	 09 BF188 11 BT165 13 BT168 13 BF155	 14 BD175 15 BD186 19 BD173	 25 BD218 26 BD210 26 BD212 27 BD280 27 BD278		
	 15 BD176 16 BD177 17 BD165 17 BD170	 14 BD175 15 BD186 19 BD173	 25 BD218 26 BD210 26 BD212 27 BD280 27 BD278		
Drive	 18 BD171 57 BW290 57 BW292	 14 BD175 15 BD186 19 BD173	 28 BD260 28 BD290 29 BLG19 30 BD215 30 BD216		
	 18 BD171 57 BW290 57 BW292	 14 BD175 15 BD186 19 BD173	 28 BD260 28 BD290 29 BLG19 30 BD215 30 BD216		
Trailer	 20 BT107	 20 BT188 21 BT160 22 BT180 22 BT161			
All-position	 41 BA106 41 BA162 58 BW291	 34 BA267 35 BA111 35 BA115 37 BA122	 33 BA202 33 BA208	 45 BD273 45 BD270 46 BD285 47 BD189	 53 BC121 53 BU123
	 41 BA106 41 BA162 58 BW291	 34 BA267 35 BA111 35 BA115 37 BA122	 36 BLR01 38 BA220	 48 BD266 48 BD276 49 BLM16 50 BD263 50 BD265	 54 BU551 54 BLC58

ALL STEEL RADIAL TIRE

Truck & Bus Tires

Long Haul/Regional/On & Off Road/Off Road/Coach & Urban




BF188

Suitable Conditions


Medium and long mileage truck running on paved and highway roads

- ✓ Low Heat Generation
- ✓ Economy and Environment Friendly
- ✓ High Wear Resistance
- ✓ Outstanding Handling and Brake Performance on Wet



Optimized structural design:

Optimized design of four layer belts to ensure driving safety and comfort.



New design tread pattern:

The straight four groove pattern design of optimized layout provides good safety and handling performance for the vehicle.

Side wall steel sheet design:

Anti tramline wear sipes designed to minimize irregular wear.



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	16.5	1054	279
CN	11R22.5	18	149/146M	8.25	3250	3000	7160	6610	930	930	135	135	16.5	1054	279
CN & VN	12R22.5	18	152/149L	9.00	3550	3250	7830	7160	930	930	135	135	17.0	1085	300
VN	11R24.5	14	146/143L	8.25	3000	2725	6610	6005	720	720	105	105	16.5	1104	279
CN & VN	11R24.5	16	149/146L	8.25	3250	3000	7160	6610	830	830	120	120	16.5	1104	279
VN	205/75R17.5	14	124/122M	6.00	1600	1500	3525	3310	750	750	110	110	13.0	753	204
CN & VN	215/75R17.5	16	135/133L	6.00	2180	2060	4805	4540	860	860	125	125	12.5	767	211
CN & VN	235/75R17.5	18	143/141L	6.75	2725	2575	6005	5675	860	860	125	125	13.0	797	233
VN	245/70R17.5	18	143/141J	7.50	2725	2575	6005	5675	875	875	125	125	13.0	789	248
CN & VN	225/70R19.5	14	128/126L	6.75	1800	1700	3970	3750	760	760	110	110	12.5	811	226
VN	245/70R19.5	18	144/142J	7.50	2800	2650	6175	5840	900	900	130	130	13.0	839	248
CN & VN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	13.5	867	262
VN	285/70R19.5	18	150/148K	8.25	3350	3150	7390	6945	900	900	130	130	14.0	895	283
CN	305/70R19.5	18	148/145M	9.00	3150	2900	6940	6395	850	850	125	125	14.5	923	305
CN & VN	255/70R22.5	16	140/137M	7.50	2500	2300	5510	5070	830	830	120	120	12.5	930	255
VN	275/70R22.5	16	148/145M	8.25	3150	2900	6940	6395	900	900	130	130	15.0	958	276
CN & VN	275/80R22.5	18	149/146L	8.25	3250	3000	7160	6610	900	900	130	130	16.0	1012	276
VN	295/60R22.5	18	150/147L	9.00	3350	3075	7390	6780	900	900	130	130	15.0	926	292
VN	295/75R22.5	14	144/141L	9.00	2800	2575	6175	5675	760	760	110	110	16.5	1014	298
VN	295/75R22.5	16	146/143L	9.00	3000	2725	6610	6005	830	830	120	120	16.5	1014	298
VN	295/80R22.5	18	152/149M	9.00	3550	3250	7825	7165	900	900	130	130	16.0	1044	298
VN	315/60R22.5	18	152/148L	9.75	3550	3150	7825	6945	900	900	130	130	14.5	950	313
VN	315/70R22.5	18	156/150L	9.00	4000	3350	8820	7390	900	900	130	130	15.5	1014	312
CN & VN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8050	850	850	125	125	17.0	1076	312
VN	315/80R22.5	20	156/150(154/150)L(M)	9.00	4000	3350	8820	7390	850	850	125	125	17.0	1076	312
VN	285/75R24.5	14	144/141L	8.25	2800	2575	6175	5675	760	760	110	110	16.5	1050	283
VN	285/75R24.5	16	147/144L	8.25	3075	2800	6780	6175	830	830	120	120	16.5	1050	283
CN	205/85R16LT	12	117/115L	5.50F	1285	1215	2835	2680	600	600	87	87	8.5	734	203
CN	10.00R20	18	149/146L	7.5	3250	3000	7160	6610	930	930	135	135	16.5	1054	278
CN	325/95R24	22	162/160K	9.0	4750	4500	10500	9920	850	850	125	125	15.0	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs



● suitable

BT165

Suitable Conditions

Medium and long mileage trucks running on paved and highway roads

- ☑ Ultra Wear Resistance
- ☑ Outstanding High Speed Performance
- ☑ Excellent Durability




● suitable



Excellent Stability on Handling:

Wider tread design, provides larger contact area, increased the stability of the trailer.



Avoid Damage on Tread:

Outstanding resistance to stone damage due to a large number of stone ejection design.



Ultra Wear Resistance:

High durability compound helps to increase the driving mileage for more than 10%.

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	8.5R17.5	12	121/120M	6.00	1450	1400	3195	3085	625	625	90	90	11.0	802	215
CN	9.5R17.5	18	143/141J	6.75	2725	2575	6005	5675	875	875	125	125	13.5	842	240
CN	9R22.5	14	136/134M	6.75	2240	2120	4940	4675	830	830	120	120	13.5	974	229
CN	10R22.5	16	144/142L	7.50	2800	2650	6175	5840	900	900	130	130	14.5	1020	254
CN	11R22.5	16	148/145M	8.25	3150	2900	6945	6395	840	840	120	120	17.0	1054	279
CN	12R22.5	18	152/149L	9.00	3550	3250	7825	7165	930	930	135	135	17.0	1085	300
CN	13R22.5	18	154/151K	9.75	3750	3450	8270	7605	830	830	120	120	17.0	1124	320
CN	225/90R17.5	14	130/128L	6.75	1900	1800	4190	3970	760	760	110	110	13.5	851	226
CN & VN	205/75R17.5	14	124/122M	6.00	1600	1500	3525	3310	750	750	110	110	13.0	753	205
CN & VN	215/75R17.5	16	135/133L	6.00	2180	2060	4805	4540	860	860	125	125	12.5	767	211
CN & VN	235/75R17.5	18	143/141L	6.75	2725	2575	6005	5675	860	860	125	125	13.0	797	233
CN	245/70R17.5	18	134/132L	7.50	2120	2000	4675	4410	900	900	130	130	13.0	789	248
CN	225/70R19.5	14	128/126L	6.75	1800	1700	3970	3750	760	760	110	110	12.5	811	226
CN	245/70R19.5	18	144/142J	7.50	2800	2650	6175	5840	900	900	130	130	13.0	839	248
CN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	13.5	867	262
CN	285/70R19.5	18	150/148K	8.25	3350	3150	7390	6945	900	900	130	130	13.0	895	283
CN	255/70R22.5	16	140/137M	7.50	2500	2300	5510	5070	830	830	120	120	13.5	930	255
CN	275/70R22.5	18	148/145M	8.25	3150	2900	6940	6395	900	900	130	130	14.5	958	276
CN	295/60R22.5	18	150/147L	9.00	3350	3075	7390	6780	900	900	130	130	14.5	926	292
CN & VN	295/80R22.5	18	154/149M	9.00	3750	3250	8270	7160	850	850	125	125	16.0	1044	298
CN	315/60R22.5	18	152/148L	9.75	3550	3150	7825	6945	900	900	130	130	14.5	950	313
CN & VN	315/70R22.5	18	156/150L	9.00	4000	3350	8820	7385	900	900	130	130	15.5	1014	312
CN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8045	850	850	125	125	17.0	1076	312
VN	315/80R22.5	20	156/150(154/150)L(M)	9.00	4000	3350	8820	7390	850	850	125	125	17.0	1076	312
CN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	123	123	15.0	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.21bs

BT168

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ☑ Low Heat Generation
- ☑ High Wear Resistance
- ☑ Long Mileage
- ☑ Low Heat Generation & Wear Resistance



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	15.0	1054	279
CN	12R22.5	18	152/149L	9.00	3550	3250	7825	7165	930	930	135	135	16.0	1085	300

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BF155

Suitable Conditions

Long mileage trucks and passenger buses running on paved and highway roads

- ☑ Low Heat Generation
- ☑ High Wear Resistance
- ☑ Outstanding High Speed Performance
- ☑ Fuel Efficiency



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12R22.5	18	152/149L	9.00	3550	3250	7830	7160	930	930	135	135	14.5	1085	300
CN	235/75R17.5	18	143/141L	6.75	2725	2527	6005	5675	860	860	125	125	13.0	797	233

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD175

Suitable Conditions

Medium and long mileage trucks running on paved and highway roads

- ☑ Low Heat Generation
- ☑ High Wear Resistance
- ☑ Excellent Grip
- ☑ Economy and Environment Friendly



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	148/145L	8.25	3150	2900	6940	6395	850	850	123	123	20.0	1059	279
CN & VN	11R22.5	16	146/143K	8.25	3000	2725	6610	6010	850	850	123	123	20.0	1065	279
CN	12R22.5	18	152/149K	9.00	3550	3250	7825	7165	930	930	135	135	20.0	1096	300
VN	12R22.5	18	152/149L	9.00	3550	3250	7830	7160	930	930	135	135	20.0	1096	300
CN	13R22.5	18	154/151K	9.75	3750	3450	8270	7605	830	830	120	120	20.5	1124	320
CN & VN	205/75R17.5	14	124/122L	6.00	1600	1500	3525	3310	750	750	110	110	15.0	753	204
CN & VN	215/75R17.5	16	135/133L	6.00	2180	2060	4805	4540	860	860	125	125	15.0	767	211
CN & VN	235/75R17.5	18	143/141L	6.75	2725	2575	6005	5675	860	860	125	125	15.0	797	233
CN	225/70R19.5	14	128/126L	6.75	1800	1700	3970	3750	760	760	110	110	15.0	811	226
CN & VN	245/70R19.5	18	144/142J	7.50	2800	2650	6175	5840	900	900	130	130	15.5	839	248
CN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	15.5	867	262
CN	255/70R22.5	16	140/137L	7.50	2500	2300	5510	5070	830	830	120	120	15.5	930	255
VN	275/80R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	22.0	1012	276
CN & VN	295/80R22.5	18	152/149M	9.00	3550	3250	7825	7165	900	900	130	130	22.0	1044	298
VN	315/70R22.5	18	156/150L	9.00	4000	3350	8820	7385	900	900	130	130	20.0	1014	312
CN & VN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8045	850	850	125	125	23.0	1076	312
VN	315/80R22.5	20	156/150(154/150)L(M)	9.00	4000	3350	8820	7390	850	850	125	125	23.0	1076	312
CN	315/80R22.5	22	158/156K	9.00	4250	4000	9370	8820	900	900	130	130	23.0	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD186

Suitable Conditions

Medium and long mileage trucks running on paved and highway roads

- ✓ Tear Resistance
- ✓ Excellent Grip
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	15.5	867	262
CN	275/70R22.5	16	148/145M	8.25	3150	2900	6945	6395	900	900	130	130	20.0	958	276
CN	285/70R19.5	18	150/148K	8.25	3350	3150	7390	6945	900	900	130	130	16.0	896	286
VN	315/60R22.5	18	152/148L	9.75	3550	3150	7825	6945	900	900	130	130	20.0	950	313

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD176

Suitable Conditions

Medium vehicles running on paved roads

- ✓ Excellent Grip
- ✓ Tear Resistance
- ✓ Long Mileage



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8045	850	850	125	125	19.5	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD177

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Low Heat Generation
- ✓ High Wear Resistance
- ✓ Outstanding Handling and Brake Performance on Wet
- ✓ Excellent CPK



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	15.5	867	262
VN	285/70R19.5	18	150/148K	8.25	3350	3150	7390	6945	900	900	130	130	16.0	895	283
VN	275/70R22.5	16	148/145M	8.25	3150	2900	6940	6395	900	900	130	130	18.0	958	276
VN	295/60R22.5	18	150/147L	9.00	3350	3075	7390	6780	900	900	130	130	18.0	926	292
VN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	7165	900	900	130	130	19.0	1044	298
VN	315/60R22.5	18	152/148L	9.75	3550	3150	7825	6945	900	900	130	130	18.0	950	313
VN	315/70R22.5	18	156/150L	9.00	4000	3350	8820	7390	900	900	130	130	19.0	1014	312
VN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8050	850	850	125	125	20.0	1076	312
VN	315/80R22.5	20	156/150(154/150)L(M)	9.00	4000	3350	8820	7390	850	850	125	125	20.0	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD165

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Low Heat Generation
- ✓ High Wear Resistance
- ✓ Excellent Grip
- ✓ Economy and Environment Friendly



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	7165	900	900	130	130	17.0	1044	298
VN	315/70R22.5	18	156/150L	9.00	4000	3350	8820	7385	900	900	130	130	18.0	1014	312
CN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8050	850	850	125	125	18.0	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD170

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ✓ Low Heat Generation
- ✓ High Wear Resistance
- ✓ Outstanding Handling and Brake Performance on Wet
- ✓ Excellent CPK



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	11R22.5	14	144/142L	8.25	2800	2650	6175	5840	720	720	105	105	22.5	1059	279
VN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	22.5	1059	279
VN	295/75R22.5	14	144/141L	9.00	2800	2575	6175	5675	760	760	110	110	22.5	1020	298
VN	295/75R22.5	16	146/143L	9.00	3000	2725	6610	6005	830	830	120	120	22.5	1020	298

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD171

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Excellent Durability



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	11R22.5	14	144/142L	8.25	2800	2650	6175	5840	720	720	105	105	23.5	1059	279
CN & VN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	23.5	1059	279
VN	11R24.5	14	146/143L	8.25	3000	2725	6610	6005	720	720	105	105	23.5	1110	279
CN & VN	11R24.5	16	149/146L	8.25	3250	3000	7160	6610	830	830	120	120	23.5	1110	279
VN	295/75R22.5	14	144/141L	9.00	2800	2575	6175	5675	760	760	110	110	23.5	1020	298
VN	295/75R22.5	16	146/143L	9.00	3000	2725	6610	6005	830	830	120	120	23.5	1020	298
VN	285/75R24.5	14	144/141L	8.25	2800	2575	6175	5675	760	760	110	110	23.5	1056	283
VN	285/75R24.5	16	147/144L	8.25	3075	2800	6780	6175	830	830	120	120	23.5	1056	283

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD173

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Adapt to Various Road Conditions



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	11R22.5	14	144/142L	8.25	2800	2650	6175	5840	720	720	105	105	21.5	1059	279
CN & VN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	21.5	1059	279
VN	11R24.5	14	146/143L	8.25	3000	2725	6610	6005	720	720	105	105	21.5	1110	279
CN & VN	11R24.5	16	149/146L	8.25	3250	3000	7160	6610	830	830	120	120	21.5	1110	279
VN	295/75R22.5	14	144/141L	9.00	2800	2575	6175	5675	760	760	110	110	21.0	1020	298
VN	295/75R22.5	16	146/143L	9.00	3000	2725	6610	6005	830	830	120	120	21.0	1020	298
VN	285/75R24.5	14	144/141L	8.25	2800	2575	6175	5675	760	760	110	110	21.0	1056	283
VN	285/75R24.5	16	147/144L	8.25	3075	2800	6780	6175	830	830	120	120	21.0	1056	283

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BT188

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Low Heat Generation
- ✓ High Wear Resistance
- ✓ Outstanding Handling and Brake Performance on Wet
- ✓ Excellent CPK



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load		Pressure		Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)	(lbs)	(kPa)	(PSI)			
VN	435/50R19.5	20	160J	14.00	4500	9920	900	130	12.5	931	438
VN	445/45R19.5	20	160J	15.00	4500	9920	900	130	13.0	895	446

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BT107

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Ultra Wear Resistance
- ✓ Excellent Stability on Handling
- ✓ Excellent Durability



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	235/75R17.5	18	143/141J	6.75	2725	2575	6005	5675	860	860	125	125	13.0	797	233
CN & VN	245/70R17.5	18	143/141J	7.50	2725	2575	6005	5675	875	875	125	125	13.0	789	248
CN	245/70R19.5	18	144/142J	7.50	2800	2650	6175	5840	900	900	130	130	13.5	839	248
VN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	13.5	867	262

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BT160

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Low Heat Generation
- ✓ High Wear Resistance
- ✓ Outstanding Handling and Brake Performance on Wet
- ✓ Excellent CPK



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load		Pressure		Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)	(lbs)	(kPa)	(PSI)			
CN & VN	385/55R22.5	20	160K	12.25	4500	9920	900	130	14.5	996	386
CN	385/65R22.5	20	160K	11.75	4500	9920	900	130	15.5	1072	389
CN & VN	385/65R22.5	24	164K	11.75	5000	11000	900	130	15.5	1072	389

S= Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BT180

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Ultra Wear Resistance
- ✓ Long Mileage
- ✓ Excellent Durability



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load		Pressure		Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)	(lbs)	(kPa)	(PSI)			
CN	385/65R22.5	20	160K	11.75	4500	9920	900	130	17.0	1072	389
CN & VN	385/65R22.5	24	164K	11.75	5000	11000	900	130	17.0	1072	389
CN	425/65R22.5	20	165K	12.25	5150	11400	830	120	16.5	1124	422

S= Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BT161

Suitable Conditions

Medium and long mileage trucks running on paved roads and highways

- ✓ Ultra Wear Resistance
- ✓ Long Life
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11.00R20	18	152/149K	8.00	3550	3250	7830	7160	930	930	135	135	16.0	1085	293

S= Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

Truck & Bus Tires

ON & OFF ROAD



BD218

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear Resistance
- ✓ Excellent Grip
- ✓ High Load Capacity



● suitable



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	9.5R17.5	18	143/141K	6.75	2725	2575	6005	5675	875	875	125	125	16.5	850	240
CN & VN	11R22.5	16	148/145L	8.25	3150	2900	6640	6395	850	850	123	123	22.5	1059	279
CN	12R22.5	18	152/149K	9.00	3550	3250	7830	7160	930	930	135	135	20.0	1096	300
VN	11R24.5	16	149/146L	8.25	3250	3000	7160	6610	830	830	120	120	22.0	1110	279
CN	225/80R17.5	18	123/122L	6.75	1550	1500	3415	3305	700	700	102	102	14.0	811	226
CN	265/70R19.5	18	143/141K	7.50	2725	2575	6005	5675	900	900	130	130	15.0	867	262
CN	275/70R22.5	18	148/145M	8.25	3150	2900	6940	6395	900	900	130	130	17.0	958	276
CN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	7165	900	900	130	130	19.0	1044	298
VN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	19.5	1096	293
VN	12.00R20	20	156/153K	8.5	4000	3650	8820	8050	900	900	130	130	21.0	1136	315
CN & VN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	125	125	20.0	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD210

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Anti Damage on Tread



● suitable



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	12R22.5	18	152/149K	9.00	3550	3250	7825	7165	930	930	135	135	22.0	1096	300
CN	13R22.5	18	154/151K	9.75	3750	3450	8270	7605	830	830	120	120	22.0	1124	320
CN	13R22.5	20	156/150J	9.75	4000	3350	8820	7390	900	900	130	130	22.0	1124	320
CN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8045	850	850	125	125	22.0	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD212

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear Resistance
- ✓ Good Grip
- ✓ Adapt to Various Road Conditions



● suitable



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11.00R20	16	150/147K	8.0	3350	3075	7390	6780	830	830	120	120	18.0	1085	293
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7160	930	930	135	135	18.0	1085	293

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD280

Suitable Conditions

Dump truck tire drive position tire used for medium and short distances on mixed road surfaces

- ✓ Tear Resistance
- ✓ Anti Damage on Tread
- ✓ Strong Constructure



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	11R22.5	16	148/145K	8.25	3150	2900	6945	6395	840	840	120	120	19.0	1059	279
CN & VN	12R22.5	18	152/149K	9.00	3550	3250	7825	7165	930	930	135	135	20.0	1096	300
CN & VN	13R22.5	20	156/150J	9.75	4000	3350	8820	7390	900	900	130	130	20.0	1124	320
CN	295/80R22.5	18	152/149K	9.00	3550	3250	7825	7165	900	900	130	130	18.0	1044	298
CN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8045	850	850	125	125	20.5	1076	312
VN	315/80R22.5	20	156/150(154/150)J(K)	9.00	4000	3350	8820	7390	850	850	125	125	20.5	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD278/BD278H

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Adapt to Various Road Conditions



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	10.00R20	18	149/146J	7.5	3250	3000	7165	6610	930	930	135	135	18.5	1065	278
CN	11.00R20	18	152/149J	8.0	3550	3250	7830	7160	930	930	135	135	19.5	1085	293
CN & VN	12.00R20	20	156/153J	8.5	4000	3650	8820	8050	900	900	130	130	20.5	1136	315
CN	12.00R20	20	156/153J	8.5	4000	3650	8820	8050	900	900	130	130	20.5	1136	315

* 12.00R20 applied to BD278H

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD260

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear Resistance
- ✓ Excellent Grip
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	7.00R16LT	14	118/114L	5.50F	1320	1180	2910	2600	770	770	110	110	14.0	785	200
CN	7.50R16LT	14	122/118L	6.00G	1500	1320	3310	2910	770	770	110	110	16.0	815	215
CN	8.25R16LT	16	128/124K	6.50H	1800	1600	3970	3530	770	770	110	110	16.0	865	235
CN	8.25R20	16	139/137K	6.5	2430	2300	5360	5070	930	930	135	135	17.5	974	236
VN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	18.5	1065	278
VN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	19.5	1096	293
VN	12.00R20	18	154/151K	8.5	3750	3450	8270	7610	830	830	120	120	21.0	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD290

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Anti Damage on Tread



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	13R22.5	20	156/150K	9.75	4000	3350	8820	7390	900	900	130	130	22.0	1136	320
VN	295/80R22.5	18	154/149L	9.00	3750	3250	8270	7160	850	850	125	125	21.0	1044	298
VN	315/80R22.5	20	156/150(154/150)J(K)	9.00	4000	3350	8820	7390	850	850	125	125	21.5	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BLG19

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear Resistance
- ✓ Excellent Grip
- ✓ Adapt to Various Road Conditions



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	9.5R17.5	18	143/141K	6.75	2725	2575	6005	5675	875	875	125	125	17.0	850	240
CN	265/70R19.5	18	143/141K	7.50	2725	2575	6005	5675	900	900	130	130	15.0	873	262
CN	8.25R16LT	16	128/124L	6.50H	1800	1600	3970	3530	770	770	110	110	15.5	865	235
CN	8.25R20	16	139/137K	6.5	2430	2300	5360	5070	930	930	135	135	17.0	974	236
CN	9.00R20	16	144/142K	7.0	2800	2650	6170	5840	900	900	130	130	18.0	1030	259
CN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	19.0	1065	278
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	20.0	1096	293
CN	12.00R20	20	156/153K	8.5	4000	3650	8820	8050	900	900	130	130	21.0	1136	315
CN	12.00R24	20	160/157K	8.5	4500	4125	9920	9090	900	900	130	130	20.0	1238	315
CN	12.00R24	22	162/160K	8.5	4750	4500	10470	9920	850	850	125	125	20.0	1238	315
CN	325/95R24	20	160/157K	9.00	4500	4125	9920	9090	900	900	130	130	20.0	1228	325

S=Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD215

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Tear and Cut Resistance
- ✓ High Stability on Handling



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	7.50R16LT	14	122/118L	6.00G	1500	1320	3310	2910	770	770	110	110	12.5	815	215
CN	8.25R16LT	18	132/128L	6.50H	2000	1800	4410	3970	870	870	126	126	13.5	865	235
CN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	15.5	1065	278
CN & VN	11.00R20	18	152/149K	8.0	3550	3250	7830	7160	930	930	135	135	17.5	1085	293
CN & VN	12.00R20	20	156/153K	8.5	4000	3650	8820	8050	900	900	130	130	18.0	1136	315

S=Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD216

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Avoid Damage on Tread



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	148/145K	8.25	3150	2900	6940	6395	850	850	123	123	24.5	1059	279
CN	11R24.5	16	149/146K	8.25	3250	3000	7160	6610	830	830	120	120	24.5	1110	279

S=Single D= Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

Truck & Bus Tires

ALL-POSITION



BA202

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads

- ✓ Tear Resistance
- ✓ Adapt to Various Road Conditions
- ✓ Excellent CPK



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8050	850	850	125	125	16.0	1076	312
CN	10.00R20	16	146/143K	7.5	3000	2725	6610	6010	830	830	120	120	17.0	1054	278
CN	11.00R20	16	150/147K	8.0	3350	3075	7390	6780	830	830	120	120	17.0	1085	293
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7160	930	930	135	135	17.0	1085	293
CN	12.00R20	22	158/155K	8.5	4250	3875	9370	8540	970	970	140	140	16.0	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA208

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads

- ✓ Ultra Wear Resistance
- ✓ Avoid Damage on Tread
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	8.25R16LT	18	132/128K	6.50H	2000	1800	4410	3970	870	870	126	126	15.0	855	235
CN	275/80R22.5	18	149/146L	8.25	3250	3000	7160	6610	900	900	130	130	16.5	1012	276

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA267

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Tear Resistance
- ✓ Reduce Stone Trapping
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	215/75R17.5	16	135/133L	6.00	2180	2060	4805	4540	860	860	125	125	15.0	773	211
CN	235/75R17.5	18	143/141L	6.75	2725	2575	6005	5675	860	860	125	125	15.0	797	233
CN	265/70R19.5	18	143/141J	7.50	2725	2575	6005	5675	900	900	130	130	15.0	867	262
VN	275/80R22.5	18	149/146L	8.25	3250	3000	7160	6610	900	900	130	130	18.5	1012	276
VN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	6945	900	900	130	130	18.0	1044	298
VN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	16.0	1054	278
VN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	17.0	1096	293

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA111

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Ultra Wear Resistance
- ✓ Long Life
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	6.50R16LT	12	110/105L	5.50F	1060	925	2335	2040	670	670	97	97	10.5	750	185
CN	7.00R16LT	14	118/114L	5.50F	1320	1180	2910	2600	770	770	110	110	11.5	775	205
CN & VN	7.50R16LT	14	122/118L	6.00G	1500	1320	3310	2910	770	770	110	110	12.5	805	215
CN	8.25R16LT	16	128/124L	6.50H	1800	1600	3970	3530	770	770	110	110	12.5	855	235

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA115

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Good Grip
- ✓ Excellent Durability



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	7.00R16LT	14	118/114L	5.50F	1320	1180	2910	2600	770	770	110	110	12.0	785	200
CN	7.50R16LT	14	122/118L	6.00G	1500	1320	3310	2910	770	770	110	110	13.0	815	215
CN	8.25R16LT	16	128/124L	6.50H	1800	1600	3970	3530	770	770	110	110	13.0	855	235
CN	8.25R16LT	18	132/128L	6.50H	2000	1800	4410	3970	870	870	126	126	13.0	855	235
CN	8.25R20	16	139/137K	6.5	2430	2300	5360	5070	930	930	135	135	14.0	974	236

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BLR01

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads

- ✓ Good Handling
- ✓ Adapt to Various Road Conditions
- ✓ Excellent CPK



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	11R22.5	16	148/145M	8.25	3150	2900	6945	6395	840	840	120	120	16.0	1054	279
CN	12R22.5	18	152/148K	9.00	3550	3150	7825	6945	850	850	125	125	16.5	1085	300
CN	13R22.5	20	156/150J	9.75	4000	3350	8820	7390	900	900	130	130	16.0	1124	320
CN	295/80R22.5	18	152/149L	9.00	3550	3250	7825	7165	900	900	130	130	17.5	1044	298
CN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8045	850	850	125	125	14.0	1076	312
CN	7.00R16LT	14	118/114L	5.50F	1320	1180	2910	2600	770	770	110	110	11.5	775	205
CN & VN	7.50R16LT	14	122/118L	6.00G	1500	1320	3310	2910	770	770	110	110	12.5	805	215
CN	8.25R16LT	14	126/122L	6.50H	1700	1500	3750	3310	670	670	97	97	12.5	855	235
CN	8.25R16LT	16	128/124L	6.50H	1800	1600	3970	3530	770	770	110	110	12.5	855	235
CN	9.00R20	16	144/142K	7.0	2800	2650	6170	5840	900	900	130	130	15.0	1019	259
CN	10.00R20	16	146/143K	7.5	3000	2725	6610	6010	830	830	120	120	16.0	1054	278
CN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	16.0	1054	278
CN	11.00R20	16	150/147K	8.0	3350	3075	7385	6780	830	830	120	120	16.5	1085	293
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	16.5	1085	293
CN	12.00R20	18	154/151K	8.5	3750	3450	8270	7610	830	830	120	120	17.0	1125	315
CN	12.00R24	20	160/157K	8.5	4500	4125	9920	9100	900	900	130	130	15.5	1226	315
VN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	123	123	15.5	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA122

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Ultra Wear Resistance
- ✓ Excellent Stability on Handling



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	146/143L	8.25	3000	2725	6610	6010	830	830	120	120	18.0	1054	279
CN	12R22.5	18	152/149L	9.00	3550	3250	7825	7165	930	930	135	135	18.0	1085	300
CN	13R22.5	18	154/151K	9.75	3750	3450	8270	7605	830	830	120	120	18.0	1124	320
CN	275/70R22.5	18	148/145K	8.25	3150	2900	6940	6395	900	900	130	130	17.0	958	276
CN	295/80R22.5	18	152/149M	9.00	3550	3250	7825	7165	900	900	130	130	17.5	1044	298
CN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8045	850	850	125	125	17.0	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA220

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads

- ✓ Ultra Wear Resistance
- ✓ High Stability on Handling
- ✓ High Load Capacity



● suitable



Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	11R22.5	16	146/143K	8.25	3000	2725	6610	6005	830	830	120	120	17.5	1054	279
CN	11R22.5	16	148/145L	8.25	3150	2900	6940	6395	850	850	123	123	17.5	1054	279
CN & VN	12R22.5	18	152/149K	9.00	3550	3250	7825	7165	930	930	135	135	18.0	1085	300
CN	13R22.5	20	156/150L	9.75	4000	3350	8820	7390	900	900	130	130	18.0	1124	320
VN	13R22.5	20	156/150K	9.75	4000	3350	8820	7390	900	900	130	130	18.0	1124	320
VN	11R24.5	14	146/143K	8.25	3000	2725	6610	6005	720	720	105	105	17.5	1104	279
VN	11R24.5	16	149/146K	8.25	3250	3000	7160	6610	830	830	120	120	17.5	1104	279
CN	295/80R22.5	18	152/149K	9.00	3550	3250	7825	6945	900	900	130	130	18.0	1044	298
CN	315/80R22.5	20	156/153L	9.00	4000	3650	8820	8050	850	850	125	125	17.0	1076	312
VN	315/80R22.5	20	156/150(154/150)L(M)	9.00	4000	3350	8820	7390	850	850	125	125	17.0	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA125

Suitable Conditions

Medium and long mileage trucks running on paved roads and highways

- ✓ Tear and Cut Resistance
- ✓ Anti Damage on Tread
- ✓ Outstanding High Speed Performance



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12R22.5	18	152/149L	9.00	3550	3250	7825	7165	930	930	135	135	15.5	1085	300
CN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	15.0	1054	278
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	15.5	1085	293
CN	12.00R20	20	156/153K	8.5	4000	3650	8820	8050	900	900	130	130	16.0	1125	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA221

Suitable Conditions

Medium and short mileage vehicles running on paved roads and highways

- ✓ Ultra Wear Resistance
- ✓ Low Heat Generation
- ✓ Long Life



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	10.00R20	18	149/146K	7.5	3250	3000	7160	6610	930	930	135	135	16.0	1054	278
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7160	930	930	135	135	16.5	1085	293

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA226

Suitable Conditions

Medium and short mileage vehicles running on paved and unpaved roads

- ✓ Tear Resistance
- ✓ Excellent Grip
- ✓ Adapt to Various Road Conditions



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load		Pressure		Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)	(lbs)	(kPa)	(PSI)			
CN & VN	385/65R22.5	24	164K	11.75	5000	11000	900	130	17.5	1072	389
CN & VN	425/65R22.5	20	165K	12.25	5150	11400	830	120	17.5	1124	422
CN	445/65R22.5	20	169K	13.00	5800	12800	900	130	17.5	1150	444

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA106

Suitable Conditions

Medium and long mileage vehicles running on paved roads

- ✓ Tear and Cut Resistance
- ✓ Anti Impact
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12.00R24	20	160/157K	8.5	4500	4125	9920	9090	900	900	130	130	14.5	1226	315
CN	12.00R24	22	162/160K	8.5	4750	4500	10470	9920	850	850	125	125	14.0	1226	315
VN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	125	125	14.5	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA162

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ✓ Ultra Wear Resistance
- ✓ Avoid Damage on Tread
- ✓ Excellent CPK
- ✓ Outstanding High Speed Performance



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	15.5	1054	279

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA105

Suitable Conditions

Medium and Short mileage vehicles running on paved and unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Avoid Damage on Tread



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12.00R24	20	160/157K	8.5	4500	4125	9920	9090	900	900	130	130	16.0	1226	315
CN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	125	125	16.0	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BA127

Suitable Conditions

Medium and short mileage vehicles running on paved and unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Avoid Damage on Tread



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	325/95R24	22	162/160K	9.00	4750	4500	10500	9920	850	850	125	125	15.5	1228	325

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

Truck & Bus Tires

OFF ROAD



BD273

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Anti Impact
- ✓ Excellent Grip



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12.00R20	20	156/153D	8.5	4000	3650	8820	8050	900	900	130	130	30.0	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD270

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	7.50R16LT	14	122/118D	6.00G	1500	1320	3310	2910	770	770	110	110	17.5	815	215
CN	8.25R16LT	16	128/124D	6.50H	1800	1600	3970	3530	770	770	110	110	17.5	865	235
CN	8.25R20	16	139/137D	6.5	2430	2300	5360	5070	930	930	135	135	19.5	974	236

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD285

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Anti Impact
- ✓ Excellent Grip



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	7.50R16LT	14	122/118D	6.00G	1500	1320	3310	2910	770	770	110	110	18.5	815	215
CN	8.25R16LT	16	128/124D	6.50H	1800	1600	3970	3530	770	770	110	110	20.0	865	235
CN	8.25R20	16	139/137D	6.5	2430	2300	5360	5070	930	930	135	135	20.0	974	236
CN	9.00R20	16	144/142D	7.0	2800	2650	6170	5840	900	900	130	130	22.0	1030	259
CN	10.00R20	18	149/146D	7.5	3250	3000	7165	6610	930	930	135	135	23.5	1065	278
CN	11.00R20	16	150/147D	8.0	3350	3075	7390	6780	830	830	120	120	24.0	1096	293
CN & VN	12.00R20	22	158/155D	8.5	4250	3875	9370	8540	970	970	140	140	24.0	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BD189

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Cut Resistance
- ✓ Excellent Grip
- ✓ Avoid Damage on Tread



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	148/145G	8.25	3150	2900	6940	6395	850	850	123	123	23.5	1065	279
CN	11R22.5	18	149/146G	8.25	3250	3000	7160	6610	930	930	123	123	23.5	1065	279
CN	12R22.5	18	152/149G	9.00	3550	3250	7830	7160	930	930	135	135	23.5	1096	300
CN	13R22.5	18	156/150G	9.75	4000	3350	8820	7390	875	875	125	125	23.5	1136	320
CN	13R22.5	20	156/150G	9.75	4000	3350	8820	7390	875	875	125	125	23.5	1136	320
CN	11R24.5	16	149/146G	8.25	3250	3000	7160	6610	830	830	120	120	23.5	1110	279
CN	275/70R22.5	16	148/145J	8.25	3150	2900	6940	6395	900	900	130	130	23.5	958	276
CN & VN	295/80R22.5	18	152/149J	9.00	3550	3250	7830	7160	900	900	130	130	23.5	1044	298
CN	315/80R22.5	20	157/154G	9.00	4125	3750	9090	8270	900	900	130	130	23.5	1076	312
CN	12.00R20	20	156/153J	8.5	4000	3650	8820	8050	900	900	130	130	23.5	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs



BD266

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Excellent Grip
- ✓ Anti Damage on Tread
- ✓ Improved Handling



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12.00R24	18	160/157D	8.5	4500	4125	9920	9090	900	900	130	130	31.0	1238	315
CN	12.00R24	20	160/157F	8.5	4500	4125	9920	9090	900	900	130	130	31.0	1238	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs



BD276

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Excellent Grip
- ✓ Reduce Stone Trapping
- ✓ Improved Handling



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12.00R24	20	160/157F	8.5	4500	4125	9920	9090	900	900	130	130	31.0	1238	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs



BLM16

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Excellent Grip
- ✓ Strong Constructure



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	13R22.5	20	156/150J	9.75	4000	3350	8820	7390	900	900	130	130	21.0	1124	320
CN	10.00R20	18	149/146K	7.5	3250	3000	7165	6610	930	930	135	135	21.0	1065	278
CN	11.00R20	16	150/147K	8.0	3350	3075	7385	6780	830	830	120	120	21.0	1096	293
CN	11.00R20	18	152/149K	8.0	3550	3250	7830	7170	930	930	135	135	21.0	1096	293
CN	12.00R20	22	158/155D	8.5	4250	3875	9370	8540	970	970	140	140	21.0	1136	315
CN	12.00R24	20	160/157K	8.5	4500	4125	9920	9090	900	900	130	130	21.5	1238	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs



BD263

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Anti Impact
- ✓ Excellent Grip



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	9.00R20	18	146/144J	7.0	3000	2800	6610	6175	970	970	140	140	21.5	1030	259
CN	12.00R20	20	156/153G	8.5	4000	3650	8820	8050	900	900	130	130	24.0	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs



BD265

Suitable Conditions

Short mileage vehicles running on unpaved roads

- ✓ Tear and Cut Resistance
- ✓ Anti Impact
- ✓ Excellent Grip
- ✓ High Load Capacity



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	12.00R20	20	156/153D	8.5	4000	3650	8820	8050	900	900	130	130	23.0	1136	315

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs



Truck & Bus Tires

COACH & URBAN



BC121

- ✓ Ultra Wear Resistance
- ✓ Superior Ride Comfort
- ✓ Outstanding Handling and Brake Performance on Wet



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	295/80R22.5	18	152/149M	9.00	3550	3250	7830	7160	930	930	135	135	15.0	1044	298

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BU551

Suitable Conditions

Short mileage vehicles running on paved roads

- ✓ Excellent Grip
- ✓ Adapt to Various Road Conditions
- ✓ Excellent Durability



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	148/145L	8.25	3150	2900	6940	6395	850	850	123	123	20.5	1054	279
CN	275/70R22.5	18	148/145J	8.25	3150	2900	6940	6395	900	900	130	130	22.0	958	276

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BU123

Suitable Conditions

Short mileage vehicles running on paved roads

- ✓ Ultra Wear Resistance
- ✓ Damage Resistance On Sidewall
- ✓ Long Life



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN & VN	11R22.5	16	148/145J	8.25	3150	2900	6940	6395	850	850	123	123	20.0	1054	279
CN & VN	275/70R22.5	18	152/148J	8.25	3550	3150	7830	6940	900	900	130	130	20.5	958	276
CN	305/70R22.5	20	153/150J	9.00	3650	3350	8050	7390	900	900	130	130	20.5	1000	305

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BLC58

Suitable Conditions

Short mileage vehicles running on paved roads

- ✓ Ultra Wear Resistance
- ✓ Damage Resistance On Sidewall
- ✓ Excellent Durability



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	10R22.5	16	144/142L	7.50	2800	2650	6175	5840	900	900	130	130	16.5	1020	254

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

Truck & Bus Tires

WINTER



BW290

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ✓ Excellent Low-temperature Performance
- ✓ Anti Damage on Tread
- ✓ Superior Traction on Snow



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	20.0	1054	279

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BW292

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ✓ Excellent Low-temperature Performance
- ✓ Excellent Stability on Handling
- ✓ Superior Traction on Snow



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
VN	275/70R22.5	16	148/145L	8.25	3150	2900	6940	6395	900	900	130	130	20.5	958	276
VN	295/80R22.5	18	152/149L	9.00	3550	3250	7830	7160	900	900	130	130	22.0	1044	298
VN	315/70R22.5	18	156/150L	9.00	4000	3350	8820	7390	900	900	130	130	20.5	1014	312
VN	315/80R22.5	20	156/153K	9.00	4000	3650	8820	8050	850	850	125	125	20.5	1076	312

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs

BW291

Suitable Conditions

Medium and long mileage truck running on paved and highway roads

- ✓ Excellent Low-temperature Performance
- ✓ Excellent CPK
- ✓ Excellent Grip



● suitable

Origin	Size	PR	LI/ SS	Standard Rim	Max. Load				Pressure				Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)
					(kgs)		(lbs)		(kPa)		(PSI)				
					S	D	S	D	S	D	S	D			
CN	11R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	20.0	1054	279
CN	225/80R17.5	14	123/122L	6.75	1550	1500	3415	3305	700	700	102	102	16.0	811	226
CN	245/70R19.5	18	144/142J	7.50	2800	2650	6175	5840	900	900	130	130	19.0	839	248
CN	265/70R19.5	16	140/138L	7.50	2500	2360	5510	5205	760	760	110	110	20.0	867	262
CN	275/80R22.5	16	146/143L	8.25	3000	2725	6610	6005	830	830	120	120	19.0	1012	276
CN	275/80R22.5	18	151/148J	8.25	3450	3150	7160	6940	900	900	130	130	19.0	1012	276

S=Single D=Dual; 1inch=25.4mm 1kPa=0.142psi 1KG≈2.2lbs