

A STANDARD THAT IS TRULY GLOBAL



WHO WE ARE

JK Tyre & Industries Ltd. is a leading Indian tyre manufacturer, ranking amongst the top 25 globally. Since 1977, we have been a trusted partner, providing superior tyre technology and performance across diverse segments – agriculture, industrial, passenger vehicles, and even mining. Our extensive network of 12 manufacturing facilities – 9 in India and 3 in Mexico – produces over 35 million tyres annually. This translates to 35 million opportunities for you to experience exceptional value and optimal performance, every single time.



PCR/SUV



PCR/SUV PATTERNS




ULTIMA NEO



ULTIMA NXT



ULTIMA SPORT



ULTIMA 210S



ULTIMA LXT



ULTIMA XPS



ELANZO TOURING



ELANZO SUPRA



UX ROYALE



RANGER H/T



RANGER A/T



RANGER M/T



RANGER X-A/T



UX ALP



UX1



UX TOURING



BLAZZE H/T



TORNADO



TAXIMAX



BLAZZE X-A/T



VECTRA



ZEPHYR



LEVITAS ULTRA

ULTIMA-NEO

SALIENT FEATURES

- Shark-winglet shoulder
- Low rolling resistance tread pattern
- Variable groove-depth
- Optimised foot print shape and pressure distribution

BENEFITS

- Serene driving comfort with secured handling performance
- Lower rolling resistance, and tread stiffness, optimised for lower wear and lower noise
- Optimised Binary Flexural Rigidity (OBFR) tread design improves steering maneuverability, proprietary tread edge designs, minimizes noise
- Ultima NEO (New Eco Optimised) for RRC wear and noise, offers better traction, ride comfort and noise levels

AVAILABLE SIZES:

175/70 R12, 165/70 R13, 175/70 R13, 185/70 R13, 145/80 R12, 145/80 R13, 155/65 R13, 155/70 R13, 155/80 R13, 165/80 R13, 155/65 R14

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
175/70 R12	H	210	80	400 A B	5.00	51	551	176
165/70 R13	H	210	79	400 A B	5.00	51	565	168
175/70 R13	T	190	82	400 A B	5.00	51	571	178
185/70 R13	H	210	86	400 A B	5.50	51	590	187
145/80 R12	T	190	74	NA	4.00	51	537	145
145/80 R13	S	180	75	NA	4.00	51	560	144
155/65 R13	T	190	73	NA	4.50	51	535	158
155/70 R13	T	190	75	400 A B	4.50	51	549	151
155/80 R13	T	190	79	400 A B	4.00	51	579	159
165/80 R13	T	190	83	400 A B	4.50	51	591	168
155/65 R14	T	190	75	NA	4.50	51	558	160



ULTIMA-NXT

SALIENT FEATURES

- Continuous centre rib
- Robust lateral blocks and hydro channels
- Unique split wing design
- Special tread compound

BENEFITS

- Better straight-line stability
- Excellent wet and dry handling
- Provided good dry and wet traction
- Excellent abrasion resistance and fuel economy

AVAILABLE SIZES:

145/70 R12, 145/80 R12, 145/80 R13, 145/70 R13, 155/70 R13

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
145/70 R12	T	190	69	NA	4.50	51	513	145
145/80 R12	T	190	74	NA	4.00	51	536	142
145/80 R13	S	180	75	NA	4.00	51	562	145
145/70 R13	T	190	71	NA	4.50	51	540	142
155/70 R13	T	190	75	NA	4.50	51	547	153



ULTIMA SPORT

SALIENT FEATURES

- Shoulder stiffness gradient optimized
- Optimized pitch sequence
- Optimized footprint shape and pressure distribution

BENEFITS

- Best cornering characteristics
- Low noise
- Better traction, ride comfort and noise levels

AVAILABLE SIZES:

185/65 R14, 185/60 R14, 165/70 R12, 165/65 R14, 165/80 R14, 195/60 R14

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
185/65 R14	H	210	86	520 A A	5.50	51	592	189
185/60 R14	H	210	82	400 A B	5.50	51	580	185
165/70 R12	T	190	77	NA	5.00	51	536	159
165/65 R14	S	180	79	400 A B	5.00	51	571	167
165/80 R14	T	190	85	400 A B	4.50	51	617	158
195/60 R14	H	210	86	400 A B	6.00	51	590	203



ULTIMA 210S

SALIENT FEATURES

- Wider tread
- Optimised pattern
- High tensile belts
- Circumferential grooves

BENEFITS

- Better road holding
- High mileage
- Good performance at high speeds with load
- Low noise
- Low aquaplaning

AVAILABLE SIZES:

195/70 R14

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
195/70 R14	S	180	95	400 A A	6.00	51	638	202



ULTIMA LXT

SALIENT FEATURES

- Extra rubber and deeper grooves
- Specially designed tread compound for better handling and stability
- Specially profiled lateral grooves for better wet and dry braking

BENEFITS

- Specially analyzed pitching sequence to ensure low noise level
- Longer durability
- Low rolling resistance and higher fuel economy

AVAILABLE SIZES:

135/70 R12, 155/65 R12

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
135/70 R12	S	180	65	NA	4.00	51	498	136
155/65 R12	S	180	71	NA	4.50	51	507	153



ULTIMA XPS

SALIENT FEATURES

- Optimised pattern design for dry and wet braking
- High abrasion resistance tread compound
- Symmetric ribs with optimised pattern stiffness

BENEFITS

- Better braking and cornering stability
- High mileage and long life
- Improved wear performance and traction

AVAILABLE SIZES:

175/70 R13

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
175/70 R13	T	190	82	NA	5.00	51	578	175



ELANZO TOURING

SALIENT FEATURES

- Symmetric touring design
- Central stability rib
- High lateral stiffness pattern
- Rolling optimised high lateral stiffness shoulder blocks
- Unique Structure Coupled Hybrid Pitch Sequence (SCHPS)

BENEFITS

- Surefooted grip and handling on highways
- Superior on-centre feel with enhanced driving stability
- Supreme grip with efficient sipe opening that assists with lateral grip, traction/braking and even smooth wear
- Improved cornering power and control in panic manoeuvre
- Quietest ever ride and highway speeds

AVAILABLE SIZES:

235/65 R17, 235/60 R18, 235/65 R18

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
235/65 R17	H	210	104	580 AA A	7.00	51	740	240
235/60 R18	V	240	103	580 AA A	7.00	51	736	234
235/65 R18	H	210	106	580 AA A	7.00	51	760	244



ELANZO SUPRA

SALIENT FEATURES

- Innovative sidewall design and apex construction
- Macho 4X4 tread pattern
- Unique open shoulder groove design

BENEFITS

- High damping load transfer, function-optimal tyre for excellent ride quality
- Excellent on centre feel and manoeuvrability for high speed applications
- Enhanced wet grip

AVAILABLE SIZES:

245/75 R16

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
245/75 R16	S	180	111	700 A B	7.00	51	773	246



UX ROYALE

SALIENT FEATURES

- Variable draft groove technology
- Waffle groove and exceptional braking features
- Stable shoulder tread blocks
- Aero-wing design
- Optimised through advanced simulation for optimum road contact
- Superior dual tread compound
- NVH optimised to lower noise

BENEFITS

- Short braking distances and high cornering stability
- Better traction, ride comfort and noise levels
- Superior safety in wet condition
- Ultra high performance at 270 kmph and 300 kmph

AVAILABLE SIZES:

185/55 R16, 175/60 R14, 175/65 R14, 175/65 R15, 175/70 R14, 185/65 R15, 185/65 R14, 185/70 R14, 195/55 R16, 195/65 R15, 205/55 R16, 205/60 R16, 205/65 R15, 205/65 R16, 215/60 R17, 215/60 R16, 215/65 R16, 235/65 R16, 225/60 R16, 225/60 R17, 215/55 R18, 175/65 R15, 205/55 R16, 175/70 R14, 195/65 R15, 205/65 R16, 165/80 R14

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
185/55 R16	H	210	83	440 A A	6.00	51	607	194
175/60 R14	H	210	79	440 A A	5.00	51	564	177
175/65 R14	H	210	82	440 A A	5.00	51	583	175
175/65 R15	H	210	84	440 A A	5.00	51	610	178
175/70 R14	H	210	84	440 A A	5.00	51	598	178
185/65 R15	H	210	88	440 A A	5.50	51	619	186
185/65 R15	T	210	88	440 A A	5.50	51	617	186
185/65 R14	H	210	86	440 A A	5.50	51	590	188
185/70 R14	H	210	88	440 A A	5.50	51	614	184
195/55 R16	V	240	87	440 A A	6.00	51	620	204
195/65 R15	V	240	91	440 A A	6.00	51	638	202
205/55 R16	V	240	91	440 A A	6.50	51	630	210
205/60 R16	V	240	92	440 A A	6.00	51	653	204
205/65 R15	V	240	94	440 A A	6.00	51	646	208
205/65 R16	H	210	95	440 A A	6.00	51	673	209
215/60 R17	H	210	96	460 A A	6.50	51	686	219
215/60 R16	V	240	95	440 A A	6.50	51	661	220
215/65 R16	H	210	98	440 A A	6.50	51	683	222
235/65 R16	T	190	103	440 A A	7.00	51	710	239
225/60 R16	V	240	98	440 A A	6.50	51	674	228
225/60 R17	H	210	99	440 A A	6.50	51	702	228
215/55 R18	H	210	95	400 A A	7.00	51	693	221
175/65 R15	H	210	84	400 A A	5.00	51	609	182
175/70 R14	H	210	84	440 A A	5.00	51	606	178
195/65 R15	V	240	91	440 A A	6.00	51	635	201
205/65 R16	V	240	95	440 A A	6.50	51	673	209
165/80 R14	T	190	85	NA	5.00	51	616	173
*215/55 R16	-	-	-	-	-	-	-	-

*To be launched soon



RANGER H/T

SALIENT FEATURES

- High traction rib design
- Extra fine sipes on tread surface
- Advanced circumferential grooves
- Solid centre and stiff shoulder design
- GA (Genetic Algorithm) noise engineering

BENEFITS

- Exceptional control and stability
- Improved traction for those occasional off-road, sand and mud tracks
- Improved safety on wet roads by efficient water dispersion
- Precise straight line and cornering steering control
- Low cabin noise for luxurious driving

AVAILABLE SIZES:

215/75 R15, 205/60 R16, 215/65 R16, 215/75 R16, 225/65 R17, 235/65 R17, 235/70 R16, 235/75 R15, 265/65 R17, 265/70 R16, 265/75 R16, 275/70 R16, 265/70 R17, 215/60 R17, 255/60 R18, 275/70 R16, 265/70 R17, 265/65 R17 LT, 255/60 R16, LT245/75 R16, LT235/85 R16, 245/65 R17, 255/65 R17, 265/70 R17, 265/70 R18, 275/65 R18, 245/60 R18

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
215/75 R15	S	180	100	460 A A	6.00	51	705	216
205/60 R16	H	210	92	460 A A	6.00	51	648	208
215/65 R16	H	210	98	460 A A	6.50	51	689	218
215/75 R16	T	190	101	460 A A	6.00	51	731	216
225/65 R17	H	210	102	460 A A	6.50	51	726	228
235/65 R17	H	210	104	460 A A	7.00	51	740	236
235/70 R16	H	210	105	460 A A	7.00	51	735	236
235/75 R15	T	190	105	460 A A	6.50	51	734	235
265/65 R17	H	210	112	460 A A	8.00	51	776	264
265/70 R16	T	190	111	460 A A	8.00	51	777	266
265/75 R16	T	190	114	460 A A	7.50	51	806	264
275/70 R16	T	190	114	460 A A	8.00	51	794	282
265/70 R17	T	190	115	460 A A	8.00	51	805	264
215/60 R17	H	210	96	460 A A	6.50	51	688	221
255/60 R18	H	210	108	460 A A	7.50	51	759	260
275/70 R16	T	190	114	460 A A	8.00	51	794	282
265/70 R17	T	190	115	460 A A	8.00	51	805	264
265/65 R17 LT	L	-	120/117	NR	-	-	777	278
*255/60 R16	-	-	-	-	-	-	-	-
*LT245/75 R16	-	-	-	-	-	-	-	-
*LT235/85 R16	-	-	-	-	-	-	-	-
*245/65 R17	-	-	-	-	-	-	-	-
*255/65 R17	-	-	-	-	-	-	-	-
*265/70 R17	-	-	-	-	-	-	-	-
*265/70 R18	-	-	-	-	-	-	-	-
*275/65 R18	-	-	-	-	-	-	-	-
*245/60 R18	-	-	-	-	-	-	-	-

*To be launched soon

(Note: - Also available in Blaze for US market)



RANGER A/T

SALIENT FEATURES

- Full depth grooves
- Variable draft groove technology
- Aggressive tread pattern
- Light truck construction in most sizes
- Larger mass tread blocks

BENEFITS

- Provides optimum road contact offering supreme grip
- Optimised pitch sequence for provide even tread wear and reduced tread noise
- Superior off road traction
- Increased puncture resistance
- Improved wear life and cut chip resistance

AVAILABLE SIZES:

215/75 R15, 235/70 R16, 31X10.5 R15, 205/70 R15C, 255/70 R15C, 215R15, 215/75 R15-RWL, 235/70 R16-RWL, 215/70 R15C

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
215/75 R15	S	180	100	300 A A	6.00	51	705	216
235/70 R16	T	190	105	300 A A	7.00	51	735	236
31X10.5 R15	Q	160	109	NA	8.50	65	773	265
205/70 R15C	S	180	106/104	NA	6.00	65	671	206
255/70 R15C	S	180	113/110	NA	7.50	65	740	260
215 R15	R	170	113	NA	6.00	65	726	218
215/75 R15-RWL	S	180	100	300 A A	6.00	51	705	216
235/70 R16-RWL	T	190	105	300 A A	7.00	51	735	236
215/70 R15C	S	180	109/107	NA	6.50	65	682	220

(Note: - Also available in Blaze for US market)



RANGER M/T

SALIENT FEATURES

- Chevron tread pattern design
- High wear resistant tread compound
- Extreme all terrain pattern with rugged shoulder design
- New generation reinforcement materials

BENEFITS

- Improved traction and better grip in mud and sand applications
- Longer life providing very low cost per km
- Better off roading performance
- Improved off roading performance & better durability in extreme conditions

AVAILABLE SIZES:

265/70 R17LT, 31X10.50 R15, LT 245/75 R16, LT 265/75 R16, LT 255/65 R18, LT 235/70 R16, LT235/85 R16, LT265/75 R16, LT235/75 R15, LT285/75 R16

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
265/70 R17LT	Q	160	118/115	NA	8.00	65	810	270
31X10.50 R15	Q	160	109	NA	8.50	50	775	275
*LT235/85 R16	-	-	-	-	-	-	-	-
*LT265/75 R16	-	-	-	-	-	-	-	-
*LT235/75 R15	-	-	-	-	-	-	-	-
*LT285/75 R16	-	-	-	-	-	-	-	-

*To be launched soon

(Note: - Also available in Blaze for US market)



RANGER X-A/T

SALIENT FEATURES

- Extreme all terrain pattern
- High tensile reinforcements
- Optimized belt vibrations
- Optimized pitch sequence and groove width through TNAP
- Optimized footprint distribution

BENEFITS

- Enhanced traction on all kind of surfaces
- High structural stability and durability on any kind of application
- Softer ride and better handling
- To reduce noise & air pumping at high speed
- Enhanced milage and grip

AVAILABLE SIZES:

31X10.5 R15 LT, 32X11.5 R15, LT235/75 R15, 215/75 R15-TT, 215/75 R15-TL, 235/75 R15-TT, 235/75 R15-TL, 235/65 R17, 265/65 R17, 265/60 R18, 255/65 R18

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
31X10.5 R15 LT	R	170	109	NA	8.50	50	774	281
32X11.5 R15	R	170	113	NA	9.00	50	798	302
LT235/75 R15	R	170	104/101	NA	6.50	50	732	233
215/75 R15-TT	S	180	100	NA	6.00	51	700	216
215/75 R15-TL	S	180	100	NA	6.00	51	700	216
235/75 R15-TT	S	180	105	NA	6.50	51	730	235
235/75 R15-TL	S	180	105	NA	6.50	51	730	235
235/65 R17	T	190	104	NA	7.00	51	740	236
265/65 R17	H	210	112	NA	8.00	51	775	272
265/60 R18	H	210	110	NA	8.00	51	775	272

(Note: - Also available in Blaze for US market)



UX ALP

SALIENT FEATURES

- Robust shoulder design and specially optimised tread blocks
- Advanced tread compound
- Optimised winter sipes with higher number of cutting edges
- Advanced sipe design and footprint optimised for snow and ice performance

BENEFITS

- Better handling stability in snow and ice, honey comb sipes generates effective wet traction, snow and ice traction
- Optimised snow handling and balanced wet slush performance
- Adaptive contour allows the footprint to develop such that tread edges are able bite in to snow and ice, removes aqua-planing, creates traction points in snow and ice

AVAILABLE SIZES:

185/65 R15, 195/65 R15, 205/60 R16

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
185/65 R15	T	190	88	NA	5.50	51	622	189
195/65 R15	V	240	91	NA	6.00	51	638	202
205/60 R16	V	240	92	NA	6.00	51	652	210



UX1

SALIENT FEATURES

- High strength, extra flexible sidewall
- Genetic algorithm used for optimised pitch sequence
- Variable groove geometry/sturdy shoulder blocks
- Specially designed asymmetric tread design

BENEFITS

- Unmatched ride comfort and durability, Specially on pothole-damaged roads
- Least noise, silent running
- Superb handling, extra grip and safety
- High speed control and better handling response

AVAILABLE SIZES:

215/50 R17, 215/55 R17, 225/55 R17, 235/45 R18, 225/60 R18, 245/40 R18, 245/45 R17, 245/45 R18, 195/55 R15, 195/60 R15, 205/60 R15, 235/55 R17, 225/50 R17, 205/55 R16

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
215/50 R17	V	240	95	480 A A	7.00	51	650	220
215/55 R17	V	240	98	480 A A	7.00	51	666	227
225/55 R17	V	240	101	480 A A	7.00	51	677	229
235/45 R18	V	240	98	480 A A	8.00	51	666	236
225/60 R18	H	210	104	480 A A	6.50	51	728	226
245/40 R18	W	270	97	480 A A	8.50	51	653	246
245/45 R17	V	240	99	480 A A	8.00	51	650	243
245/45 R18	W	270	100	480 A A	8.00	51	676	243
195/55 R15	V	240	89	480 A A	6.00	51	598	197
195/60 R15	V	240	92	480 A A	6.00	51	619	207
205/60 R15	V	240	95	480 A A	6.00	51	629	214
235/55 R17	V	240	103	480 A A	7.50	51	695	245
225/50 R17	V	240	98	480 A A	7.00	51	658	228
205/55 R16	V	240	94	480 A A	6.50	51	633	212
*215/45 R17	-	-	-	-	-	-	-	-
*225/45 R17	-	-	-	-	-	-	-	-
*235/45 R17	-	-	-	-	-	-	-	-
*225/40 R18	-	-	-	-	-	-	-	-
*225/45 R18	-	-	-	-	-	-	-	-
*255/40 R18	-	-	-	-	-	-	-	-
*235/55 R18	-	-	-	-	-	-	-	-

*To be launched soon



UX TOURING

SALIENT FEATURES

- Highest UTQG rated tyre
- Touring tread design with specialised central rib
- High control design pattern and robust shoulder blocks
- GA (Genetic Algorithm) noise engineering

BENEFITS

- Best in class tyre life, traction and cooler running
- Precise straight line steering control and comfortable journeys
- Supreme lateral grip and stable cornering on long drives
- Low cabin noise for luxurious driving

AVAILABLE SIZES:

165/65 R14, 165/70 R14, 165/80 R14, 185/65 R14, 185/60 R15, 185/65 R15, 195/55 R16, 175/65 R14, 205/65 R16, 175/60 R15, 205/65 R15, 215/45 R17, 225/45 R17, 235/45 R17, 225/40 R18, 225/45 R18, 255/40 R18, 235/55 R18

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
165/65 R14	T	190	79	NA	5.00	51	568	170
165/70 R14	S	180	81	NA	5.00	51	590	166
165/80 R14	S	180	85	NA	4.50	51	614	169
185/65 R14	H	210	86	NA	5.50	51	600	197
185/60 R15	T	190	84	NA	5.50	51	606	188
185/65 R15	H	210	88	NA	5.50	51	619	186
195/55 R16	H	210	87	480 A A	6.00	51	620	204
175/65 R14	T	190	82	NA	5.00	51	582	178
205/65 R16	H	210	95	480 A A	6.00	51	672	206
175/60 R15	H	210	81	NA	5.00	51	592	176
205/65 R15	V	240	94	480 A A	6.00	51	646	212

Image simulated for illustrative purpose only.



BLAZZE H/T

SALIENT FEATURES

- Robust tread blocks
- Open shoulder design
- High tread depth
- Unique sipe design
- Special tread compound

BENEFITS

- Excellent traction, braking and uniform pressure distribution
- Excellent traction and heat dissipation
- Higher initial tyre mileage
- Improved wet traction and grip
- Excellent abrasion resistance and fuel economy

AVAILABLE SIZES:

215/75 R15, 205/60 R16, 215/65 R16, 215/75 R16, 225/65 R17, 235/65 R17, 235/70 R16, 235/75 R15, 265/65 R17, 265/70 R16, 265/75 R16, 275/70 R16

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
215/75 R15	S	180	100	460 A A	6.00	51	705	216
205/60 R16	H	210	92	460 A A	6.00	51	648	208
215/65 R16	H	210	98	460 A A	6.50	51	689	218
215/75 R16	T	190	101	460 A A	6.00	51	731	216
225/65 R17	H	210	102	460 A A	6.50	51	726	228
235/65 R17	H	210	104	460 A A	7.00	51	740	236
235/70 R16	H	210	105	460 A A	7.00	51	735	236
235/75 R15	T	190	105	460 A A	6.50	51	734	235
265/65 R17	H	210	112	460 A A	8.00	51	776	264
265/70 R16	T	190	111	460 A A	8.00	51	777	266
265/75 R16	T	190	114	460 A A	7.50	51	806	264
275/70 R16	T	190	114	460 A A	8.00	51	794	282



TORNADO

SALIENT FEATURES

- 4 rib symmetric design
- Higher NSD
- Optimized wet braking
- Steel belts with high cutting resistance

BENEFITS

- Optimized high speed performance , better dry grip and steering
- Excellent mileage and durability.
- Most efficient water drainage from center of contact patch
- High cutting resistance, least creep and best dimensional stability

AVAILABLE SIZES:

175/70 R13, 165/80 R14, 175/65 R14, 155/65 R13, 165/65 R13 , 155/70 R13

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
175/70 R13	T	190	82	300 A B	5.00	51	577	176
165/80 R14	S	180	85	NA	4.50	51	615	163
175/65 R14	T	190	82	YES	5.00	51	581	179
155/65 R13	T	190	73	NA	4.50	51	534	155
165/65 R13	T	190	77	NA	5.00	51	546	168
155/70 R13	S	180	75	NA	4.50	51	548	156



TAXIMAX

SALIENT FEATURES

- Exclusively designed tread compound wear and tear resistant
- Double steel belted sidewall
- Specially designed buttoned rib
- Unique design for reduced vibrations

BENEFITS

- Best in class tyre life
- Excellent durability against cut and burst
- Excellent grip and braking
- Extra comfort for rigorous driving

AVAILABLE SIZES:

165/80 R14, 175/65 R14, 145/80 R13, 155/80 R13, 185/60 R15, 185/65 R15, 185/70 R14, 165/65 R14, 165/70 R14, 205/65 R16, 145/80 R12-TT, 145/80 R12-TL, 205/65 R15, 155/70 R13, 145/70 R13

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
165/80 R14	S	180	85	NA	4.50	51	616	158
175/65 R14	T	190	82	NA	5.00	51	582	178
145/80 R13	T	190	75	NA	4.00	51	562	147
155/80 R13	T	190	79	NA	4.50	51	579	155
185/60 R15	T	190	84	NA	5.50	51	606	185
185/65 R15	H	210	88	NA	5.50	51	619	186
185/70 R14	T	190	88	NA	5.50	51	618	187
165/65 R14	T	190	79	NA	5.00	51	566	165
165/70 R14	S	180	81	NA	5.00	51	590	166
205/65 R16	H	210	95	NA	6.00	51	672	205
145/80 R12-TT	T	190	74	NA	4.00	51	536	147
145/80 R12-TL	T	190	74	NA	4.00	51	533	147
205/65 R15	V	240	94	NA	6.00	51	645	207
155/70 R13	T	190	75	NA	4.50	51	549	154
145/70 R13	T	190	71	NA	4.50	51	540	150



BLAZZE X-A/T

SALIENT FEATURES

- Extreme all terrain pattern
- High tensile reinforcements
- Optimized belt vibrations
- Optimized pitch sequence & groove width through TNAP
- Optimized footprint distribution

BENEFITS

- Enhanced traction on all kinds of surfaces
- High structural stability and durability on any kind of application
- Softer ride and better handling
- Reduced noise and air pumping at high speed
- Enhanced mileage and grip

AVAILABLE SIZES:

31X10.5 R15, 32X11.5 R15, LT235/75 R15

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
31X10.5 R15 LT	R	-	109	NA	8.50	50	774	281
32X11.5 R15	R	-	113	NA	9.00	50	798	302
LT235/75 R15	R	-	104/101	NA	6.50	50	732	233



VECTRA

SALIENT FEATURES

- Wider contact patch
- Exclusive tread block pattern
- High aesthetics

BENEFITS

- Excellent traction and grip on wet and dry surfaces
- Combines all-terrain traction with a quiet highway ride
- Enhances the visual appeal of the vehicle

AVAILABLE SIZES:

185/70 R14, 195/65 R15, 205/60 R16, 175/65 R14, 155/80 R13, 155/70 R14, 165/70 R14, 175/70 R14, 185/60 R15, 185/65 R15, 175/65 R14

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
185/70 R14	T	190	88	440 A B	5.50	51	613	186
195/65 R15	H	210	91	440 A B	6.00	51	638	203
205/60 R16	V	240	92	440 A B	6.00	51	650	203
175/65 R14	H	210	82	440 A B	5.00	51	581	177
155/80 R13	S	180	79	NA	4.50	51	578	157
155/70 R14	T	190	77	NA	4.50	51	574	157
165/70 R14	T	190	81	NA	5.00	51	585	167
175/70 R14	T	190	84	NA	5.00	51	602	184
185/60 R15	T	190	84	NA	5.50	51	603	192
185/65 R15	T	190	88	440 A B	5.50	51	619	187
175/65 R14	T	190	82	400 A B	5.00	51	585	175



ZEPHYR

SALIENT FEATURES

- Extra supple sidewalls
- Curved grooves coupled with angular sipes
- Optimised tread distribution

BENEFITS

- Comfortable ride and reduced vibration during high speed manoeuvring
- Most efficient water drainage from centre of contact patch
- Uniform tread wear

AVAILABLE SIZES:

195/65 R15, 205/65 R15

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
195/65 R15	V	240	91	NA	6.00	51	638	203
205/65 R15	V	240	94	NA	6.00	51	650	206



LEVITAS ULTRA

SALIENT FEATURES

- Highly stiff, asymmetric tread design
- Optimized groove drafts, angled lateral features with stable centre
- Specially engineered tri-tread configuration for optimum grip and high speed endurance
- Optimized pitch sequence cancels noise effectively

BENEFITS

- This has a particularly positive effect on handling and cornering
- Providing fine steering precision and responsive feedback to the driver
- Short braking distances in dry and wet conditions
- Quite running at all speeds

AVAILABLE SIZES:

225/45 R17, 245/45 R17, 225/55 R17, 235/55 R17, 225/55 R16, 225/50 R17, 245/45 R18

SIZE	SPEED RATING	KMPH	LOAD INDEX	UTQG	RIM WIDTH (INCH)	MAX PRESSURE (PSI)	UNLOADED INFLATED TYRE DIMENSION	
							OUTER DIAMETER (MM)	SECTIONAL WIDTH (MM)
225/45 R17	Y	300	94	NA	7.50	51	631	229
245/45 R17	W	270	99	NA	8.00	51	650	240
225/55 R17	Y	300	101	NA	7.00	51	686	235
235/55 R17	Y	300	103	NA	7.50	51	697	249
225/55 R16	W	270	99	NA	7.50	51	658	237
225/50 R17	Y	300	98	NA	7.00	51	662	230
245/45 R18	W	300	100	NA	8.00	51	682	245





JKTYRE & INDUSTRIES LTD.

ADMINISTRATIVE OFFICE

3, Bahadur Shah Zafar Marg, New Delhi - 110002

Ph.: +91 011-66001112, 011-66001122 | email: exports@jkmail.com | Fax: +91 1123322059

REGISTERED OFFICE

Jaykaygram, PO-Tyre Factory, Kankroli-313 342, Rajasthan